



OVER 40 YEARS OF
DEPENDABLE EQUIPMENT
FOR PROGRESSIVE FARMING

VINE CONDITIONER

Speed Up Combining
With KMC's 4 & 6-Row
Folding Vine Conditioner



6-ROW FOLD-

- Allows peanuts to dry faster, permitting combining earlier in the morning, earlier in the season.
- Cleans dirt and foreign material for improved grades.
- Fluff and lift vines while returning windrow to previous inverted position.

SPECIFICATIONS	4-ROW FOLDING	6-ROW FOLDING
Approximate Weight	1500 lbs	2,250 lbs
Required Horsepower	15 - 30 hp	25 - 50 hp
PTO Speed	540 - 1000 RPM	540 - 1000 RPM
Overall Width	158" unfolded (108" folded)	226" unfolded (138" folded)
Height	41" unfolded (106" folded)	41" unfolded (106" folded)
Length	71"	71"
Hitch	Cat II, III, Cat III & IIIN Quick Hitch	Cat II, III, Cat III & IIIN Quick Hitch

Features:

- Folds compactly with standard 8" hydraulic cylinders for convenience. (Folding Only)
- Equipped with safety transport straps.
- Belt drive for smooth, quiet operation. PTO and other drive train components shielded for safety.
- Slip clutch protected. (Folding Only)
- Small diameter pickup rollers and long 13-bar (64" wide) chain drive rattler bars for gentler lifting, better soil and rock removal.
- Sloped pickup teeth designed to minimize wrapping without reducing pickup efficiency.
- Handles six 36", or 38" rows.
- Optional dirt knocker kit for greater soil and rock removal.
- Wings float for a better job on terraced or uneven fields. (Folding Only)
- Strong, sturdy construction throughout.
- 5 x 8 gauge wheels (4).



The KMC 6R-30 Rigid Vine Conditioner:



KELLEY MANUFACTURING CO.

80 Vernon Drive / Zip 31794
 P.O. Drawer 1467 / Zip 31793
 Tifton, GA



Tel: 229-382-9393
 Toll Free: 1-800-444-5449
 Fax: 229-382-5259
 Email Address: info@kelleymfg.com

SPECIFICATIONS:	6-ROW (30")
Approximate Weight	2000 lbs
Horsepower Required	25-50 hp
PTO Speed	540/1000
Width of Pick-up	3 x 64"
Overall Width	186"
Height	41"
Length	71"
Hitch	Cat II, III, Cat III & IIN Quick Hitch