



www.kelleymfg.com / 1-800-444-5449

Over 40 Years of Dependable
Equipment for Progressive
Farming

Dirt Pan

**The Ready-To-Work
Scraper**



Models:
S450 (4 1/2 yds)
S600 (6 yds)
S800 (8yds)

Kelley Manufacturing Co.
80 Vernon Drive / P.O. Drawer 1467
Tifton, Ga. 31793

...Just Hitch Up And Go!!!!

- Level your crop fields and improve drainage control.*
- Clear your surface vegetation.*
- Transform your pasture into crop land.*
- Clean and maintain feed lots, barns and grain bins.*
- Clean-out poultry houses.**
- Maintain rural roads.*
- Build levees and ponds.*
- Faster and more economical than conventional land moving.*
- Many more uses!!!**

Cuts, loads, transports, and dumps the upper layer of dirt with speed and efficiency!!

- The best in land forming equipment.
- The prices include all "the extras." Even the draw bar pin is provided, along with a host of quality-plus features you'll find nowhere else.
- Delivered complete and ready for work, the Scraper saves your time - and money.
- The Scraper is available in 4.5, 6, and 8-cubic yard sizes, in two- and four-wheel models.

Clam Style Dirt pan built heavy duty with 1/4 in. steel!!!



Low profile bucket with bolted on blade to reduce HP requirements and save fuel consumption.





Formed Hydraulic Lines produce minimum velocity loss and heat buildup for longer cylinder life, and insure efficient operation on the hardest of ground.



Reversible Cutting Edge doubles blade life and insures efficient operation on the hardest of ground.

Flexible Hitch Design permits scraper to follow roughest terrain and eliminates problems and breakage in ball joints.



Heavy-Duty Welding adds extra strength to make the KMC Scraper the toughest, hardest-to-kill land-forming tool available today.

Stinger Blade optional on all models.



Single Hydraulic Control lever lets operator handle the scraper with one standard tractor remote for ease in operation.

Replacement Spindles, with extra-heavy duty wheels and hubs, are bolted rather than welded in place to permit rapid changes.



High-Flotation Tires eliminate frame strain for easy rolling on all types of terrain to eliminate tractor strain.

Model	S450	S600	S800
TYPE	FOLLOW	LEAD/FOLLOW	LEAD/FOLLOW
CAPACITY (HEAPED)	4 1/2 YARDS (APPROX.)	6 YARDS (APPROX.)	8 YARDS (APPROX.)
DEPTH OF CUT	3 INCHES	3 INCHES	3 INCHES
CUTTING WIDTH	6 FEET	6 FEET	6 FEET
CARRYING HEIGHT	10 INCHES	11 INCHES	11 INCHES
HYDRAULIC REQUIREMENTS	1500 P.S.I.	1500 P.S.I.	1500 P.S.I.
TIRES	11L-15 SL (2) 10 Ply	14L-16.1 SL (2) 8 Ply	13.6-16.1 (4) 8 Ply
WEIGHT	3720	3960	4660
HP REQUIREMENTS Not to exceed 225 HP on any model!	130	160	180