



*OVER 40 YEARS OF
DEPENDABLE EQUIPMENT
FOR PROGRESSIVE FARMING*

HEAVY-DUTY KMC POULTRY HOUSE CLEANERS

Standard Equipment for 4250



Reinforced leveler bars with heavier 667X chain. Same size as unloader chain.



Larger and stronger leveler chains with 1 1/2" diameter shafts. Sprockets and bearings are larger to accommodate chain.



Larger sifter and leveler motors (34% larger on sifter, 45% larger on leveler). All motors mounted inboard for more side clearance.



Re-enforced feeder reel.

For More Information, Call KMC or Your Nearest KMC Dealer!

KMC Poultry House Cleaners for fast and easy clean out!



Model 4250

Specifications:

	Model 4200	Model 4200LP
Weight	With Tandem Axle Wheels: 5,570 lbs. With Single Axle Wheels: 5,345 lbs.	With Tandem Axle Wheels: 5,400 lbs. With Single Axle Wheels: 5,180 lbs.
Width	90"	90"
Height (Working)	74"	64"
Length	270"(with or without spreader)	270"(with or without spreader)
Pickup Width	72"	72"
Tank Capacity	165 cubic feet	135 cubic feet
Tire Size	Tandem Axle Model: 9.5L x 15 (8 ply) Single Axle Model: 12.5L x 16 (8 ply)	Tandem Axle Model: 9.5L x 15 (8 ply) Single Axle Model: 12.5L x 16 (8 ply)
Conveyors	667X Pintle chain on floor conveyor; 662 on loading, leveling conveyors	667X Pintle chain on floor conveyor; 662 on loading, leveling conveyors
Tongue	Swivel clevis, manual side adjustment	Swivel clevis, manual side adjustment
Depth Control	Raised, lowered (from tractor) with hydraulic cylinder	Raised, lowered (from tractor) with hydraulic cylinder
Hydraulic Pump	Mounts to tractor PTO shaft, 540 RPM	Mounts to tractor PTO shaft, 540 RPM
Blade	Beveled, high strength steel	Beveled, high strength steel
Recommended HP	55 - 65 HP Tractor	55 - 65 HP Tractor

Kelley Manufacturing Co.
 P.O. Drawer 1467 80 Vernon Drive
 Tifton Georgia 31793 1-800-444-5449 www.kelleymfg.com